AEGIS inc.

RDMS DocID 111267

Environmental Consultants

MARCH 1997 SEMI-ANNUAL GROUND WATER QUALITY MONITORING REPORT

500 South Broad Street
Meriden, Connecticut

Conducted:
March 11, 1997 Through March 12, 1997

RCRA Identification No. CTD047713136

Prepared For:
S. Lane Cree Barry, Senior Vice President
DEVCON ENTERPRISES, INC.
Corporate Center West
433 South Main Street - Suite 300
West Hartford, Connecticut 06110

***Aegis, Inc.* Project No. 0307050L**

Report Issued:
June 16, 1997

Prepared By:
Aegis, Inc.

Scot Kuhn
Environmental Geologist

Michael D. Zaliznock
Principal Environmental Scientist

DEVCON ENTERPRISES, INC.

CORPORATE CENTER WEST • 433 SOUTH MAIN STREET • SUITE 300 • WEST HARTFORD, CT 06110 • 860-521-6999 • FAX: 860-521-6789

June 18, 1997

Michael O'Brien
US Environmental Protection Agency
HRW-CAN3
JFK Federal Building
Boston, MA 02203

Re: 1997 Semi-Annual Ground Water Quality Monitoring Report
Silver Hill Business Center, 500 South Broad Street, Meriden, Connecticut
RCRA Identification Nº CTD047713136
Aegis Project Nº 0307050L

Dear Mr. O'Brien:

Enclosed is a copy of the Semi-Annual Ground Water Quality Monitoring Report for the above-referenced facility. The monitoring period discussed in this report covers the first half of the 1997 calendar year. As you know, the Connecticut Department of Environmental Protection (CTDEP) approved a reduction in sampling frequency from quarterly to a semi-annual basis in December 1996. The next scheduled sampling event is planned for September 1997.

This report was prepared in accordance with the requirements of U.S. Environmental Protection Agency (USEPA) Code of Federal Regulation 40 CFR 265; and with the CTDEP Regulation 22a-449(c). A copy of this report has been submitted to Peter Ploch of the Connecticut Department of Environmental Protection.

If you have any questions regarding this report, please contact this office.

Sincerely,

S. Lane Cree Barry
Senior Vice President

Enclosure

c:workin\0307L197.doc

MARCH 1997 SEMI-ANNUAL GROUND WATER QUALITY MONITORING REPORT

500 South Broad Street
Meriden, Connecticut

***Aegis, Inc.* Project No. 0307050L**

TABLE OF CONTENTS

APPENDICES

1.0 INTRODUCTION

1.1 Site Location

The site is currently part of the Silver Hill Business Center located at 500 South Broad Street (west side) in the City of Meriden, New Haven County, Connecticut (refer to Figure 1, Appendix A). The property is located within a mixed industrial / commercial / residential area, and is approximately 600 feet south of the intersection of South Broad Street (a.k.a. Connecticut Route 5) and South Broad Terrace. The corporate boundary dividing the City of Meriden and the Town of Wallingford is located approximately 400 feet north of the site.

1.2 Purpose

The purpose of this report is to document the procedures used to collect ground water samples from select on-site monitoring wells; to evaluate water quality changes and trends; and to present the results of the ground water quality monitoring conducted during the March 1997 sampling event.

Ground water samples are currently collected on a semi-annual basis from 5 wells installed in the vicinity of a former on-site waste water treatment system (WTS). The monitoring program is conducted to evaluate temporal and spatial fluctuations in ground water and ground water quality, and to further assess contaminant impact to the site. This WTS is regulated by the Resource Conservation and Recovery Act (RCRA).

1.3 Applicable Regulatory Requirements

The investigations presented in this report were conducted in accordance with the following requirements:

Pursuant to USEPA §40 CFR 270.73(g) and §22a-449(c)-110 of the Connecticut Hazardous Waste Management Regulations (CHWMR), owners or operators of any hazardous waste management facility, as defined in §40 CFR 270.2 and §22a-449(c)-110 of the CHWMR, which achieved interim status prior to November 8, 1984, were required to submit a Part B application for a RCRA permit for the facility by November 8, 1988. Interim status facilities for which Part B applications were not filed by November 8, 1988 lost interim status on November 8, 1992. In accordance with §40 CFR 265.112(d)(3)(i) and §22a-449(c)-105 of the CHWMR, owners or

operators must submit a Closure Plan for their facility to the Regional Administrator and the Commissioner no later than fifteen days after termination of interim status.

a. Regulations of Connecticut State Agencies Hazardous Waste Management Regulations, 22a-449(c), Sections 1 through 42, and Section 29 - Closure and Post Closure. A RCRA Closure Plan for the WTS was prepared by *Aegis, Inc.* in March 1994.

b. CFR 265.0, Interim Status Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities; Section 265.197 - Closure and Post Closure. A RCRA Closure Plan for the WTS was prepared by *Aegis, Inc.* in March 1994.

c. Administrative Order HM-640, State of Connecticut versus South Broad Street; requiring South Broad Associates to abate pollution in compliance with Connecticut's Hazardous Waste Management Regulations.

1.4 Report Authors / Client Contact

This report was authored by Michael D. Zaliznock and Scot Kuhn of *Aegis, Inc.* Questions regarding this report may be directed to either individual. The client contact for this project is:

Ms. S. Lane Cree Barry
Devcon Enterprises, Inc.
433 South Main Street - Suite 300
West Hartford, CT 06110

1.5 Date of Study / Scope of Services

The ground water sampling was conducted on March 12, 1997. The scope of work included in this report includes the following:

a. The elevations of the static ground water levels were gauged in each of the 12 on-site monitoring wells, and the resulting static water elevations were tabulated and mapped.

b. Ground water samples were collected from 5 of the 12 on-site monitoring wells by *Aegis, Inc.*, personnel and submitted to state-certified testing laboratories under chain-of-custody procedures for quantitative analyses.

c. Field data, including pH, temperature, dissolved oxygen, and specific conductance, were collected from each of the sampled wells; the results were tabulated; and the findings were evaluated for changes and trends.

d. The laboratory analytical results were tabulated and graphed to evaluate developing ground water quality changes and trends.

1.6 Limitations

This report was prepared by *Aegis, Inc.* for the sole use of South Broad Associates, owner of 500 South Broad Street, and its legal counsel in connection with an assessment of the site ground water and hydrogeologic conditions. The work was undertaken to perform a ground water quality investigation in the vicinity of the subject property's RCRA Regulated Unit in accordance with the Connecticut Hazardous Waste Management Regulations, the USEPA 40 CFR Section 265.197 - Closure and Post Closure, and with generally accepted engineering and hydrogeologic practices. No other warranty, expressed or implied, is made. Absolute assurance that any and all possible contamination at the site was identified cannot be provided.

The report conclusions are based, in part, on information provided by the client, their agents or third parties. *Aegis, Inc.* assumes no responsibility as to the accuracy or completeness of this information. Where visual observations are included in the report, they represent conditions at the time of the investigation, and may not be indicative of past or future site conditions.

2.0 BACKGROUND SUMMARY

The site comprises approximately 33.6 acres of land which was developed in 1956 with two non-residential buildings. Prior to site development, the property was reportedly utilized for agricultural purposes (orchards). One building (approximately 8,600 square feet) consists of a former meeting hall presently occupied by the Silver Hill YMCA. The other building (approximately 380,000 square feet) once housed the former International Silver Company (Insilco) manufacturing facility. This building is currently occupied by offices of the Silver Hill Business Center.

The former Insilco facility was used for the manufacture of metal plated hollowware (tableware) from 1956 until 1983, when Insilco and various subsidiaries ceased operations. In 1983, World Tableware International (WTI) continued a small manufacturing division at the site, and manufactured nickel-silver hollowware. Waste waters produced by these operations were treated on-site, to some capacity, from approximately 1965 to 1987. Manufacturing waste waters produced by WTI were stored on-site for removal by a hauler. WTI ceased manufacturing at the site in April 1987.

On December 1, 1983, the property was purchased by Devcon Enterprises of Hartford, Connecticut, and by Central Bank for Savings, Meriden, Connecticut. South Broad Associates was a corporation organized by the owners to manage the property and lease space in the building.

The water treatment system (WTS), located on the northwest side of the manufacturing building, is regulated under the Resource Conservation and Recovery Act (RCRA). The WTS was used by the facility, to some capacity, from approximately 1965 to 1987. A building housing the WTS treatment equipment (an equalization tank and clarifier) was removed from the site prior to 1984.

Presently, five (5) underground storage tanks (UST's), the concrete floor and foundation of the former WTS building, and the associated underground utilities remain on-site. Neither the UST's nor the WTS are currently used. The specific locations of the WTS and the UST's on the subject property are shown on Figure 2 in Appendix A.

The existing on-site buildings are served by public drinking water and sanitary sewers provided by the City of Meriden. There are no known public or private drinking water supply wells in close proximity to the subject property.

The site is generally level, gently sloping from the east to the west towards the WTS. However, the topographic relief west of the WTS drops steeply from an elevation of approximately 250 feet (ft) above mean sea level (MSL) down to 110 ft, at a gradient of approximately 0.23 ft/ft, where it abuts an undeveloped parcel along the westernmost property boundary. Stormwater runoff generally follows the site topography, with a gradual slope downward to the west, away from South Broad Street.

The property is bounded on the south and east (across South Broad Street) by undeveloped land and commercial properties, and on the north and west by residential / undeveloped land.

2.1 Monitoring Well Installations

Thirteen (13) ground water monitoring wells (MW) were installed on the property during various subsurface investigations conducted between 1989 and 1995. Six wells (MW-1, MW-2, MW-3, MW-4, MW-5, and MW-6) were installed during investigations conducted by Con-Test, Inc. in 1989. In 1992, Fuss & O'Neill installed five additional wells (MW-7, MW-8, MW-9, MW-10, and MW-11). Of these eleven initial wells, only MW-4 and MW-8 are located proximal to the RCRA Closure Unit. Monitoring well MW-6 was paved over during previous on-site work and has not been successfully located. The remaining upgradient well (MW-1) was damaged in September 1996 and replaced on December 6, 1996.

Because additional wells were needed to better assess the area of the RCRA Closure Unit, two wells (MW-12 and MW-13) were drilled on February 20, 1995. The wells were drilled by Sima Drilling Company of Cheshire, Connecticut, as supervised by a representative of *Aegis, Inc.* The 2-inch diameter wells were installed in the overburden using a hollow stem auger drilling rig. Both wells were drilled to a depth of 25 feet below grade, and constructed with 10 foot sections of slotted #304 stainless steel screen, extending approximately 2 feet above the water table. Solid polyvinylchloride (PVC) risers, with threaded joints, were extended to grade as the well casing.

The screened sections and a portion of the PVC casing were filter packed with #1 Morie sand to a depth of 9 feet below grade (3 feet above the well screen). Each well was sealed with a 3 foot layer of bentonite chips. Both wells were installed with a 4-inch diameter steel well protector (rising 2 to 3 feet above grade), anchored with a 2 foot collar of concrete. Each well casing was fitted with a watertight plug and locking cover.

The wells were developed by pumping until the water appeared free of sediment. The waters resulting from the development of the wells, and the waters generated from equipment cleaning, were collected and stored on-site until the analytical results of the ground water samples were received and the disposal options reviewed.

The details associated with the collection and field screening of soil samples collected during the installation of monitor wells MW-12 and MW-13 are presented in the *Aegis, Inc.* "RCRA Closure Plan Monitoring Well and Compliance Monitoring Report", dated May 23, 1994.

The location of each of the monitoring wells is illustrated in Figure 2 of Appendix A. Copies of the drilling logs, the drilling permits, and/or the well completion reports for the wells subject to this report (MW-1/MW-1(R), MW-4, MW-8, MW-12, and MW-13) are included in Appendix C.

2.2 Monitoring Well Replacement

Monitoring well MW-1, located in the northeast corner of the property, was originally installed in March 1988, as a 2-inch polyvinyl chloride (PVC) well to a depth of 15 feet. The well was drilled by C.E. Pratt & Son drilling company under the supervision of Con-Test. The well was damaged in September 1996 during construction and paving activities associated with the development of the Pep Boys vehicle service facility.

Monitoring well MW-1 was replaced on December 6, 1996, and renamed MW-1(R). The replacement work was conducted by Sima Drilling Company, Cheshire, Connecticut, and supervised by *Aegis, Inc.* The original well was over-drilled using a hollow stem auger to a maximum depth of 18 feet below grade. The well was replaced with 2-inch diameter schedule 40 PVC casing, including the placement of a 10-foot section of #10 slot PVC well screen installed at the bottom of the borehole. The solid PVC well casing was threaded to the top of the well screen and extended to the ground surface.

The annular space between the well screen and the borehole was backfilled with number one sand, to within 6 feet of surface grade (approximately 2 feet above the well screen). Approximately 3 feet of bentonite pellets were placed above the well screen. Native soil was used to backfill the annular space to within 1.5 feet of surface grade. The remaining annular space was filled with a concrete slurry. The well was completed with a flush mount road box, locking expansion cap, and

a bolted protective cover. Copies of the new well boring log and completion report are included in Appendix C.

The elevation and location of monitoring well MW-1(R) were surveyed to the Connecticut Geodetic Survey (CGS) datum on December 24, 1996. At that time, the well was developed and approximately five well volumes of ground water were purged.

2.3 Existing Monitoring Program

Five (5) overburden monitoring wells (MW-1(R), MW-4, MW-8, MW-12 and MW-13) are located in the vicinity of the RCRA Closure Unit (the former waste water treatment plant). These wells are presently sampled on a semi-annual basis as part of an ongoing monitoring program to develop a database, evaluate temporal fluctuations in ground water quality, and further assess contaminant impact to the site. Well MW-1(R), located in the northeast corner of the property, represents the upgradient background monitoring well. The remaining four (4) wells are positioned downgradient of the Closure Unit.

Static water level measurements are being collected from each of the 12 wells on-site to monitor the physical characteristics of the aquifer over time and to assess the potential for migration of the contamination off-site.

3.0 ENVIRONMENTAL SETTING

3.1 Floodplains / Inland Wetlands and Watercourses

According to City of Meriden Flood Insurance Map, Community Panel #090081-0005B, the site is not located within a flood hazard zone. Information obtained through the City of Meriden Inland Wetlands and Watercourses office indicated that the site does not contain inland wetlands or watercourses. However, directly south of the property, a strip of Wilbraham very stony silt loam, which is classified as an Inland Wetlands Soil by the Soil Conservation Service, is present. This area appears to be a drainage swale collecting stormwater runoff from the site.

3.2 Soil Classifications

According to the Soil Conservation Survey for New Haven County, the site is underlain by soils described as Urban Land and Wethersfield loam. Urban Land is characterized as soils located in areas that are covered by buildings, paved roads, and parking lots. Wethersfield loam is a gently sloping, well drained soil usually found on the top of drumlins, hills and ridges, and glacial uplands. Typically, the surface soil is dark-brown loam, the subsoil reddish-brown, and the substratum (up to 60 inches) is a reddish-brown, very fine sandy loam. The topographic features within the area of the RCRA Closure Unit indicate that the soils primarily consist of fill material of unknown composition.

3.3 Surficial and Bedrock Geology

According to the Surficial Geology Map of the Meriden Quadrangle, the site is located upon ground-moraine till deposits, associated with layers of stratified drift. The till is predominately fine-grained and compact, and ranges from pale reddish-brown to dark brownish-red. The Bedrock Geological Map of Connecticut indicates that the surficial materials are underlain by New Haven Arkose that is highly compact and fractured. Arkose is a sandstone-like sedimentary rock, known locally as brownstone.

3.4 Surface Water / Classification / Drainage

According to the Natural Drainage Basins Map of Connecticut, the site is located within the South Central Coast Basin, and the Quinnipiac River regional and sub-regional basins. The Quinnipiac River is located approximately 0.40 miles west of the site, with Meetinghouse Brook located approximately 0.40 miles east of the site.

The DEP has classified the reach of the Quinnipiac River nearest the site as Class "C/B" quality. This classification means that these waters do not presently meet the water quality standards which support its designated uses. The State's goal is to restore the surface water to Class "B" quality and attain Class "B" designated uses (i.e., recreational uses, fish and wildlife habitat, and agricultural and industrial water supply). The site is not located within a public drinking water supply watershed area.

3.5 Ground Water Classification

The ground water beneath the site is classified as "GB/GA" quality. This classification indicates that the ground water may not be suitable for direct human consumption without treatment due to waste discharges, spills, leaks of chemicals, and/or land use impacts. The State's goal is to restore the ground water to "GA" quality. The site is not located within the zone of contribution of a public drinking water supply well or well field.

4.0 GROUND WATER SAMPLING METHODOLOGY

Ground water samples were collected from 5 on-site overburden monitoring wells (MW-1(R), MW-4, MW-8, MW-12, and MW-13) on March 12, 1997. The purpose of the monitoring is to develop a ground water quality database, to evaluate temporal and spatial fluctuations in ground water quality, and to further assess contaminant impact to the site. The well locations are depicted on Figure 2 (Appendix A).

Using surveyed wells, depth to ground water measurements were collected from each of the 12 existing wells on March 11, 1997 to determine total hydraulic heads and generate ground water elevation contours. The static ground water levels were measured using a Solinst® electronic water level indicator. Ground water contours were generated from this data to identify the ground water seepage direction and planar hydraulic gradient. The ground water depths and elevations are summarized in Table 1 (Appendix B). Ground water elevations were plotted versus time on hydrographs provided in Appendix E.

On the day of sample collection (March 12, 1997), approximately three well volumes of water were purged from wells MW-1(R), MW-4, MW-8, MW-12, and MW-13, using a new, dedicated, disposable, polyethylene bailer. The purging was conducted to ensure collection of ground water samples representative of formation water.

After purging the wells, the pH, specific conductivity, and water temperatures were collected using an Oakton™ water testing meter. The dissolved oxygen concentration was also measured in the field using a YSI™ dissolved oxygen meter. The field data was used to determine whether a sufficient quantity of water was bailed from each well to provide a sample representative of ground water. The ground water samples were collected after three generally consistent conductivity, pH, temperature and dissolved oxygen readings were obtained. The field analysis results are summarized in Table 3 (Appendix B).

Each of the wells sampled generally contained some degree of reddish-brown silt. According to EPA studies, high turbidity in the ground water may affect the analytical results for the sample. Furthermore, traditional sampling practices do not differentiate between the chemical species dissolved in the water and those sorbed to mobile particles that are being transported by ground water. As a result, the detected concentrations may not have been representative of the truly dissolved constituents in the water.

water. As a result, the detected concentrations may not have been representative of the truly dissolved constituents in the water.

Consequently, *Aegis, Inc.* attempted to minimize the turbidity levels in the ground water by implementing a lower flow purging and sampling technique. This technique was initiated during the December 1995 round of testing, which consists of withdrawing the sampling bailers at a slower rate than used during previous sampling events. Although this procedure increased the time required for sampling each well, the turbidity levels were lower than in the past.

The water samples were collected into appropriate clean containers, labeled, preserved, and sealed. The samples were stored on ice and delivered under chain-of-custody to state-certified laboratories the same day of sample collection. In order to validate the analytical results of volatile parameters, trip blanks were also prepared prior to sampling. The trip blanks consisted of distilled water known to contain no detectable volatile organic compounds.

5.0 HYDRAULIC GRADIENT

Hydraulic head data for this site has been obtained from 12 overburden monitoring wells presently installed on-site. Ground water beneath this site is present in an unconfined aquifer (water table aquifer) at depths of approximately 1 to 19 feet below surface grade, across the site, with a seasonal fluctuation of about 5 feet.

The hydraulic gradient beneath the site was calculated using depth to water measurements collected on March 11, 1997 (Table 1, Appendix B). The measured water table elevation in the overburden wells across the site ranged from approximately 0.97 (MW-5) to 19.09 feet (MW-9) below surface grade. Ground water contours generated this quarter identify a south / southwest direction of ground water flow; and a horizontal ground water gradient of approximately 0.03 feet/foot (Figure 2, Appendix A). This is generally consistent with previously reported ground water flow directions and pressure gradients.

In addition to tabulating ground water elevation data, each of the wells were graphed versus time, to evaluate ground water elevation variances and seasonal fluctuations across the site. The differences in ground water elevations at each given point combined with seasonal fluctuations, can be used to determine the hydraulic characteristics of an aquifer.

Combined with field measurement data, the hydrographs can also be used to evaluate the potential of surface water interference. A graph of the historical ground water hydrograph data is provided in Appendix E.

6.0 LABORATORY ANALYSES AND RESULTS

The ground water samples were submitted to *Aegis, Inc.* Environmental Laboratory Services, Rocky Hill, Connecticut to be analyzed for halogenated and aromatic volatile organic hydrocarbons (EPA Method 8021). Connecticut Testing Laboratories, Inc., Meriden, Connecticut conducted the analyses for total petroleum hydrocarbons (TPH) per EPA Method 418.1; total metals (arsenic, antimony, barium, beryllium, cadmium, chromium, copper, lead, mercury, nickel, selenium, silver, thallium, tin, and zinc) per EPA Methods 200.7-282.1; hexavalent chromium per EPA Method 218.4; total and amenable cyanides per EPA Methods 335.2 and 335.1, respectively; total organic carbon (TOC) per EPA Method 415.2; fecal coliform bacteria per EPA Method 9222; and pH per EPA Method 150.1.

The laboratory analytical results are summarized in Table 2, Appendix B. Copies of the laboratory reports are included in Appendix D. Graphs of the historical ground water quality data are provided in Appendix F. The results of the analyses found the following:

- The laboratories reported no detectable levels of arsenic, antimony, barium, beryllium, silver, cadmium, chromium (total and hexavalent), copper, lead, mercury, nickel, selenium, thallium, tin, zinc, TPH, amenable cyanide, or fecal coliform bacteria in any of the ground water samples. The trip blank tested free of hydrocarbons.

- Total organic carbon was detected in each of the four wells, in concentrations ranging from 1.4 milligrams per liter (mg/L) in wells MW-1(R) and MW-8 to 2.6 mg/L in MW-4. Total cyanide was detected in MW-13 at 0.09 mg/L. The pH levels measured in all four wells ranged from 6.0 in MW-1(R) to 6.7 in MW-12.

- Trichloroethylene, a volatile organic hydrocarbon, was detected in well MW-8 at 9 micrograms per liter (µg/L).

7.0 SUMMARY AND CONCLUSIONS

The ground water quality associated with the RCRA Regulated Unit located at 500 South Broad Street, Meriden, Connecticut was monitored on a quarterly basis between March 1995 and September 1996, and on a semi-annual basis (per State approval) since September 1996. The findings of the March 1997 sampling event are summarized as follows:

a. The former facility was used by Insilco for the manufacture of metal plated hollowware (tableware) from 1956 until approximately 1983. In 1983, World Tableware International (WTI) continued a small manufacturing division at the site, and manufactured nickel-silver hollowware. Manufacturing waste waters produced by WTI were stored on-site for removal by a hauler. WTI ceased manufacturing at the site in April 1987.

b. The facility regulated under RCRA for this site is an inactive water treatment system (WTS), which is located on the northwest side of the manufacturing building. The WTS was used by the manufacturing facility, to some capacity, since approximately 1965. A building housing the WTS treatment equipment (an equalization tank and clarifier) was removed from the site prior to 1984.

c. Thirteen (13) ground water monitoring wells were installed on the property during various subsurface investigations completed between 1989 and 1995. Six (6) wells (MW-1, MW-2, MW-3, MW-4, MW-5, and MW-6) were installed during investigations conducted by Con-Test, Inc. in 1989. In 1992, Fuss & O'Neill installed five (5) additional wells (MW-7, MW-8, MW-9, MW-10, and MW-11). Two (2) additional wells (MW-12 and MW-13) were installed by *Aegis, Inc.* in 1995. Well MW-6 was paved over and unable to be located for testing. Monitoring well MW-1 was damaged during construction activities of a nearby facility (Pep Boys) and was replaced in December 1996. The well was renamed MW-1(R).

d. Five (5) monitoring wells (MW-1(R), MW-4, MW-8, MW-12, and MW-13) are associated with the subsurface investigation of the RCRA Closure Unit (the inactive waste water treatment plant). These wells are presently sampled on a semi-annual basis as part of an ongoing monitoring program to develop a database, to evaluate temporal fluctuations in ground water quality, and to further assess contaminant impact to the site. Well MW-1(R), located in the northeast corner of the property, represents the upgradient background monitoring well. The remaining four (4) wells are positioned downgradient of the regulated unit.

e. Ground water samples were collected from the five monitoring wells on March 12, 1997. The turbidity levels in the ground water samples previously collected during earlier sampling events (March 1995 through September 1995 sampling) were observed to be high. EPA studies suggest that high turbidity in the ground water may result in elevated levels of metals due to their sorption onto the sediments in the water. In an attempt to minimize the turbidity levels, a lower flow purging and sampling technique was implemented. This procedure has been used since December 1995 and consists of withdrawing the sampling bailers at a slower rate, which significantly lowers the observed turbidity levels in the samples.

f. Static water level measurements are collected from each of the 12 wells on-site to monitor the physical characteristics of the aquifer over time; determine the effects of seasonal fluctuations on ground water contamination; and to assess the potential for migration of the contamination off-site. Overburden ground water beneath the site is present in an unconfined aquifer at depths of approximately 1 to 19 feet below surface grade, across the site, with a seasonal fluctuation of about 5 feet.

g. Ground water contours generated this quarter identify a south / southwest direction of ground water flow; and a horizontal ground water gradient of approximately 0.03 feet/foot (Figure 2, Appendix A). This is generally consistent with previously reported ground water flow directions and hydraulic pressure gradients.

h. The laboratories reported no detectable levels of arsenic, antimony, barium, beryllium, silver, cadmium, chromium (total and hexavalent), copper, lead, mercury, nickel, selenium, thallium, tin, zinc, TPH, amenable cyanide, or fecal coliform bacteria in any of the ground water samples collected during this semi-annual monitoring event. The trip blank tested free of hydrocarbons.

i. Monitoring well MW-1(R) has been tested 7 times since its installation. During this time, several heavy metals (barium, chromium, copper, lead, nickel, and zinc), and the chlorinated compound 1,1,1-trichloroethane, have been detected in the well. No metals or halogenated compounds were identified in the sample collected from this well during this sampling event. The pH of the water collected from MW-1(R) was measured at 6.0. Levels of total organic carbon (TOC) remained generally stable between 1.0 and 1.6 mg/L. TOC was measured at 1.4 mg/L in March 1997.

j. Monitoring well MW-4 has been tested 11 times since its installation in 1989. During this time, several heavy metals (arsenic, barium, beryllium, cadmium, total and hexavalent chromium, copper, lead, nickel, and zinc), and the chlorinated compound 1,1,1-trichloroethane have been detected in the well. No metals or halogenated compounds were identified in the sample collected from well MW-4 during this sampling event. The pH of the water collected from MW-4 was measured at 6.6. Levels of total organic carbon (TOC) have remained generally stable between 2.1 and 4.2 mg/L. TOC was measured at 2.6 mg/L in March 1997.

k. Monitoring well MW-8 has been tested on 9 separate occasions since its installation in 1992. During this time, several heavy metals (barium, beryllium, chromium, copper, lead, nickel, and zinc) and the chlorinated compounds trichloroethylene, 1,1,1-trichloroethane, and tetrachloroethylene have been detected in the well. With the exception of trichloroethylene (9 µg/L), no metals or halogenated compounds were identified in this well during this sampling event. The pH of the water collected from MW-8 was measured at 6.4. Levels of total organic carbon (TOC) have remained generally stable between 1.0 and 1.7 mg/L. TOC was measured at 1.4 mg/L in March 1997.

l. Monitoring well MW-12 has been tested 8 times since its installation in February 1995. During this time, several heavy metals (barium, beryllium, total and hexavalent chromium, copper, lead, nickel, and zinc) and the chlorinated compound trichloroethylene have been detected in the well. No metals or halogenated compounds were identified in the sample collected from well MW-12 during this sampling event. The pH of the water collected from MW-12 was measured at 6.7. Levels of total organic carbon (TOC) have generally ranged from below detectable limits to 2.1 mg/L. TOC was measured at 1.8 mg/L in March 1997.

m. Monitoring well MW-13 has been tested 8 times since its installation in February 1995. During this time, several heavy metals (barium, beryllium, chromium, copper, lead, nickel, and zinc), total cyanide, and the chlorinated compounds trichloroethylene, 1,1,1-trichloroethane, and 1,1-dichloroethane have been detected in the well. With the exception of total cyanide (0.09 mg/L), No metals or halogenated compounds were identified in the sample collected from well MW-13 during this sampling event. The pH of the water collected from MW-13 was measured at 6.2. Levels of total organic carbon (TOC) have remained generally stable between 1.1 and 1.9 mg/L. TOC was measured at 1.6 mg/L in March 1997.

8.0 RECOMMENDATIONS

In accordance with the DEP Remediation Standard Regulations, §22a-133k-3(g)(3), ground water quality monitoring should continue on a semi-annual basis. Consultations with DEP personnel should be ongoing in order to adjust the monitoring program according to analytical results of the wells, and with other on-site work.

REFERENCES

- Connecticut Department of Environmental Protection, Water Management Bureau, Water Quality Standards, adopted January, 1992. Effective date May 15,1992.
- Regulations of Connecticut State Agencies, Remediation Standard Regulations, Connecticut General Statutes Sections 22a-133k-1 to 22a-133k-4', adopted December 13, 1995.
- Connecticut Department of Environmental Protection, Water Compliance Unit, Adopted Water Classifications for the South Central Coast Major Basin, April 17, 1985.
- Connecticut Department of Environmental Protection, Water Management Bureau, Leachate and Waste Water Discharge Sources for the South Central Coast Basin, May 1989.
- Bedrock Geologic Map of the Meriden, Connecticut Quadrangle, United States Department of the Interior, United States Geological Survey, 1968.
- Surficial Geology of the Meriden, Connecticut Quadrangle, United States Department of the Interior, United States Geological Survey, 1962.
- United States Department of the Interior Geological Survey, Meriden, Connecticut Quadrangle, 7.5 Minute Series, Photo revised 1984.
- United States Department of Agriculture Soil Conservation Service, Soil Survey of New Haven County, July 1979.
- Federal Emergency Management Agency, Flood Insurance Map, Community Panel #090081-0005B, September 26, 1982.
- Hanshaw, Penelope M., Surficial Geology of Meriden Quadrangle, U.S. Geological Survey, 1962.
- *Aegis, Inc.* RCRA Closure Plan - Document 1 - Facility Information and Site Characterization Work Plan for 500 South Broad Street, Meriden, Connecticut, dated March 1994.
- Melvin, Robert, et al, - The Stratigraphy and Hydraulic Properties of Tills in Southern New England, U.S. Geological Survey Open File Report 91-481, dated 1995.

APPENDIX A

FIGURE 1 - SITE LOCATION MAP

FIGURE 2 - MARCH 12, 1997 SITE PLAN AND GROUND WATER ISOPLETH MAP

AEGIS PROJECT NO. 0307



Figure 1 – Site Location Map – 500 South Broad Street, Meriden, Connecticut.
Portion taken from U.S.G.S. Topographic Map for Meriden, Connecticut Quadrangle.
7.5 Minute Series (Topographic)



UTM GRID AND 1984 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

CONTOUR INTERVAL 10 FEET

NATIONAL GEODETIC VERTICAL DATUM OF 1929



QUADRANGLE LOCATION

1967
PHOTOREVISED 1984

AEGIS ENVIRONMENTAL CONSULTANTS, INC. 2138 SILAS DEANE HIGHWAY, ROCKY HILL, CT. 06067 TEL (860) 563-1041 FAX (860) 529-5124

LEGEND

⊕	–	MONITORING WELL LOCATION
UST	–	UNDERGROUND STORAGE TANK
AST	–	ABOVE-GROUND STORAGE TANK
CB	–	CATCH BASIN
EL.	–	ELEVATION (feet) [Connecticut Geodetic Survey Datum]
240	–	GROUND SURFACE CONTOUR LINE
238.00	–	GROUND WATER CONTOUR LINE (MARCH 1997)

[redacted]

NOTES:

1) CONTOUR INTERVAL IS 2.0 FEET.
2) MW-11 IS INSTALLED IN BEDROCK AND WAS NOT USED TO CONSTRUCT THE OVERBURDEN GROUND WATER CONTOURS.
3) MW-1 DAMAGED IN SEPTEMBER 1996 AND REPLACED IN MARCH 1997.
4) MW-1 THROUGH MW-6 INSTALLED UNDER CONTEST SUPERVISION.
5) MW-7 THROUGH MW-11 INSTALLED UNDER FUSS & O'NEILL SUPERVISION.
6) MW-12, MW-13, AND MW-1(R) INSTALLED UNDER AEGIS, INC. SUPERVISION.

PLAN COMPILED FROM INFORMATION ON:

- "U.S.G.S. TOPOGRAPHIC MAP FOR MERIDEN, CT", PHOTOREVISED 1984.
- "TOPOGRAPHIC PLAN OF MERIDEN, CT", MAP NO. 87, DATED APRIL 1965.
- "BOUNDARY MAP OF PROPERTY OF SOUTH BROAD ASSOCIATES, 500 SOUTH BROAD STREET, MERIDEN, CT", REVISED 06-21-85.
- "TREATMENT PLANT EXPANSION PLOT PLAN & CONTOURS", DWG NO. 5-E-134, DATED 10-13-69.
- "NEW HOLLOWARE FACTORY MAP OF UNDERGROUND SERVICES MID-SOUTH SECTION" DWG NO. 5-E-1-2, REVISED 01-04-79.

2138 Silas Deane Highway
Rocky Hill, CT 06067-2315
FAX (860) 529-5124
Environmental Consultants

CLIENT	SOUTH BROAD ASSOCIATES
	500 SOUTH BROAD STREET, MERIDEN, CONNECTICUT
PROJECT	COMPLIANCE MONITORING
DRAWING TITLE	MARCH 1997 SITE PLAN AND GROUND WATER ISOPLETH MAP
PROJECT NO.	03070501
DATE:	4/4/95 REV: 05/19/97
SCALE :	AS NOTED
DRAWN BY :	J.C.J.
DWG NO.	686 03070512

FIGURE 2

APPENDIX B

TABLE 1 - HISTORICAL GROUND WATER HYDROGRAPH DATA

TABLE 2 - HISTORICAL GROUND WATER QUALITY DATA

TABLE 3 - HISTORICAL GROUND WATER FIELD MEASUREMENT DATA

TABLE 1

(Sheet 1 of 3)

Historical Ground Water Hydrograph Data

500 South Broad Street, Meriden, Connecticut

Well ID	Surveyed Well Protector Elev. (ft)	Well Bottom Elevation (ft)	Well Screen Length (ft)	Monitoring Event	Measured Depth to Water (ft)	Ground Water Elevation (ft)
MW-1	263.44	246.68	10.00	04/11/89	11.26	252.18
				01/04/93	11.61	251.83
				03/08/95	12.21	251.23
				06/28/95	Dry	Dry
				09/27/95	Dry	Dry
				12/18/95	15.30	248.14
				03/13/96	10.37	253.07
				06/12/96	12.83	250.61
				09/18/96	Damaged	Damaged
MW-1(R)	263.84	246.05	10.00	03/12/97	12.36	251.48
MW-2	255.82	239.15	10.00	04/11/89	6.30	249.52
				01/08/93	6.94	248.88
				03/08/95	NM	NM
				06/28/95	8.95	246.87
				09/27/95	10.91	244.91
				12/18/95	7.68	248.14
				03/13/96	5.48	250.34
				06/12/96	6.93	248.89
				09/18/96	8.60	247.22
				03/12/97	6.40	249.42
MW-3	256.77	238.45	10.00	04/11/89	7.64	249.13
				01/04/93	7.78	248.99
				03/08/95	NM	NM
				06/28/95	8.61	248.16
				09/27/95	10.56	246.21
				12/18/95	9.31	247.46
				03/13/96	6.03	250.74
				06/12/96	6.28	250.49
				09/18/96	7.58	249.19
				03/12/97	6.04	250.73
MW-4	238.15	222.52	10.00	04/11/89	3.60	234.55
				01/04/93	5.06	233.09
				03/08/95	5.71	232.44
				06/28/95	9.45	228.70
				09/27/95	Dry	Dry
				12/18/95	7.88	230.27
				03/13/96	4.51	233.64
				06/12/96	7.30	230.85
				09/18/96	10.39	227.76
				03/12/97	5.06	233.09

Notes: Depth to water measured from the well protector of each well.

NM - not measured.

Aegis, Inc.

c:\work\n\0307DATA.WK4

TABLE 1

(Sheet 2 of 3)

Historical Ground Water Hydrograph Data

500 South Broad Street, Meriden, Connecticut

Well ID	Ground Elevation (ft)	Well Bottom Elevation (ft)	Well Screen Length (ft)	Monitoring Event	Measured Depth to Water (ft)	Ground Water Elevation (ft)
MW-5	246.82	235.05	10.00	04/11/89	2.14	244.68
				01/04/93	2.86	243.96
				03/08/95	NM	NM
				06/28/95	6.53	240.29
				09/27/95	8.38	238.44
				12/18/95	4.51	242.31
				03/13/96	2.30	244.52
				06/12/96	5.36	241.46
				09/18/96	4.65	242.17
				03/12/97	2.59	244.23
MW-6*	NM	NM	NM	NM	NM	NM
MW-7	PVC Elevation 253.25 Protector Damaged	228.68	10.00	01/04/93	18.31	235.08
				03/08/95	NM	NM
				06/28/95	21.45	231.80
				09/27/95	24.04	229.21
				12/18/95	20.08	233.17
				03/13/96	17.40	235.85
				06/12/96	19.12	234.13
				09/18/96	20.60	232.65
				03/12/97	17.60	235.65
MW-8	256.38	229.49	10.00	01/04/93	20.71	235.67
				03/08/95	20.84	235.54
				06/28/95	23.38	233.00
				09/27/95	26.24	230.14
				12/18/95	22.01	234.37
				03/13/96	20.22	236.16
				06/12/96	21.14	235.24
				09/18/96	23.56	232.82
				03/12/97	20.47	235.91
MW-9	255.31	223.38	15.00	01/04/93	22.38	232.93
				03/08/95	NM	NM
				06/28/95	25.01	230.30
				09/27/95	26.72	228.59
				12/18/95	23.66	231.65
				03/13/96	20.86	234.45
				06/12/96	22.38	232.93
				09/18/96	24.88	230.43
				03/12/97	21.80	233.51

Notes: Depth to water measured from the well protector of each well.

NM - not measured.

* - Monitor Well MW-6 was paved over prior to the January 1993 sampling event and could not be located.

Aegis, Inc.

c:\worldn\0307DATA.WK4

TABLE 1

(Sheet 3 of 3)

Historical Ground Water Hydrograph Data

500 South Broad Street, Meriden, Connecticut

Well ID	Ground Elevation (ft)	Well Bottom Elevation (ft)	Well Screen Length (ft)	Monitoring Event	Measured Depth to Water (ft)	Ground Water Elevation (ft)
MW-10	257.63	226.75	10.00	01/04/93	21.95	235.68
				03/08/95	NM	NM
				06/28/95	24.03	233.60
				09/27/95	26.21	231.42
				12/18/95	22.78	234.85
				03/13/96	19.86	237.77
				06/12/96	20.94	236.69
				09/18/96	23.89	233.74
				03/12/97	21.02	236.61
MW-11	255.94	212.47	20.00	01/04/93	15.43	240.51
				03/08/95	NM	NM
				06/28/95	16.78	239.16
				09/27/95	18.64	237.30
				12/18/95	16.73	239.21
				03/13/96	13.76	242.18
				06/12/96	14.35	241.59
				09/18/96	15.53	240.41
				03/12/97	14.33	241.61
MW-12	254.15	227.02	10.00	03/08/95	19.43	234.72
				06/28/95	22.46	231.69
				09/27/95	25.43	228.72
				12/18/95	20.82	233.33
				03/13/96	18.31	235.84
				06/12/96	20.34	233.81
				09/18/96	22.74	231.41
				03/12/97	19.15	235.00
MW-13	256.72	229.31	10.00	03/08/95	21.23	235.49
				06/28/95	23.82	232.90
				09/27/95	26.77	229.95
				12/18/95	22.39	234.33
				03/13/96	20.51	236.21
				06/12/96	21.63	235.09
				09/18/96	24.04	232.68
				03/12/97	21.00	235.72

Notes: Depth to water measured from the well protector of each well.

NM - not measured.

Aegis, Inc.

c:\worldn\0307DATA.WK4

TABLE 2

(Sheet 1 of 2)

Historical Ground Water Quality Data

500 South Broad Street, Meriden, Connecticut

Well ID	Sample Event	Foot Note	PARAMETER																									
			pH	T. Cn	A. Cn	TPH	TOC	F. Coli	T. Sb	T. As	T. Ba	T. Be	T. Cd	T. Cr	Cr6	T. Cu	T. Pb	T. Hg	T. Ni	T. Se	T. Ag	T. Tl	T. Sn	T. Zn	TCE	TCA	PCE	11DCA	CFM
MW-1**	04/11/89	1	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	<1.0	<1.0	<1.0	<1.0	<1.0
	01/05/93	2	NA	<.01	NA	<.5	NA	NA	NA	ND<	z	NA	ND<	ND<	NA	NA	ND<	ND<	0.05	ND<	ND<	NA	NA	NA	<1.0	<1.0	<1.0	<1.0	<1.0
	03/08/95	3	6.2	ND<	ND<	ND<	1.3	ND<	<.05	ND<	2.2	<.1	ND<	2.70	NA	0.21	0.240	ND<	0.28	ND<	ND<	<.5	NA	0.88	ND<	1.0	ND<	ND<	ND<
	06/29/95	3	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
	09/27/95	3	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
	12/19/95	3	6.6	ND<	ND<	ND<	1.2	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
	03/14/96	3	6.0	ND<	ND<	ND<	1.6	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.10	ND<	ND<	ND<	ND<	ND<
	06/13/96	3	6.0	ND<	ND<	ND<	1.0	ND<	ND<	ND<	0.5	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.23	ND<	ND<	ND<	ND<	ND<
	09/16/96	3	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
MW-1(R)	03/12/97	3	6.0	ND<	ND<	ND<	1.4	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
MW-4	04/04/89	1	NA	NA	NA	NA	NA	NA	NA	0.03	0.6	NA	0.16	<.05	NA	NA	<.05	<.0003	0.23	<.005	<.05	NA	NA	NA	NA	NA	NA	NA	NA
	04/11/89	1	NA	<.02	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	<1.0	<1.0	<1.0	<1.0	<1.0
	04/30/92	3	NA	NA	NA	NA	NA	NA	NA	<.05	<.5	NA	<.01	0.09	NA	NA	0.180	<.002	NA	<.01	<.01	NA	NA	NA	<1.0	<1.0	<1.0	<1.0	<1.0
	01/05/93	2	NA	<.01	NA	<.5	NA	NA	NA	ND<	z	NA	ND<	z	NA	NA	z	ND<	0.13	ND<	ND<	NA	NA	NA	<1.0	<1.0	<1.0	<1.0	<1.0
	03/08/95	3	6.6	ND<	ND<	ND<	4.9	ND<	<.05	ND<	0.5	<.1	ND<	0.08	NA	0.54	0.100	ND<	0.16	ND<	ND<	<.5	NA	0.36	ND<	2.0	ND<	ND<	ND<
	06/29/95	3	6.6	ND<	ND<	ND<	3.1	ND<	ND<	ND<	1.0	0.011	ND<	0.20	NA	0.37	0.200	ND<	0.15	ND<	ND<	ND<	ND<	0.59	ND<	ND<	ND<	ND<	ND<
	09/27/95	3	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
	12/19/95	3	6.5	ND<	ND<	ND<	3.9	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
	03/14/96	3	6.6	ND<	ND<	ND<	4.2	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.11	ND<	ND<	ND<	ND<	ND<
	06/13/96	3	6.6	ND<	ND<	ND<	2.3	ND<	ND<	ND<	ND<	ND<	ND<	0.05	ND<	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.18	ND<	ND<	ND<	ND<	ND<
	09/16/96	3	6.7	ND<	ND<	ND<	2.1	ND<	ND<	ND<	0.6	ND<	ND<	0.13	0.13	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.34	ND<	ND<	ND<	ND<	ND<
	03/12/97	3	6.6	ND<	ND<	ND<	2.6	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
MW-8	01/05/93	2	NA	<.01	NA	<.5	NA	NA	NA	ND<	z	NA	ND<	ND<	NA	NA	ND<	ND<	0.18	ND<	ND<	NA	NA	NA	8.5	2.3	<1.0	<1.0	<1.0
	03/08/95	3	6.8	ND<	ND<	ND<	1.0	ND<	<.05	ND<	0.8	<.1	ND<	ND<	NA	0.10	0.024	ND<	ND<	ND<	ND<	<.5	NA	0.46	10.0	4.0	5.0	ND<	ND<
	06/29/95	3	6.9	ND<	ND<	ND<	1.4	ND<	ND<	ND<	1.6	0.017	ND<	0.05	NA	0.26	0.021	ND<	0.09	ND<	ND<	ND<	ND<	0.61	7.0	2.0	3.0	ND<	ND<
	09/27/95	3	7.3	ND<	ND<	ND<	1.1	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.03	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.05	12.0	ND<	2.0	ND<	ND<
	12/19/95	3	6.6	ND<	ND<	ND<	1.1	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	9.0	ND<	3.0	ND<	ND<
	03/14/96	3	6.5	ND<	ND<	ND<	1.7	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.11	5.0	ND<	ND<	ND<	ND<
	06/13/96	3	6.5	ND<	ND<	ND<	1.2	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.19	20.0	8.0	14.0	ND<	ND<
	09/16/96	3	6.7	ND<	ND<	ND<	1.2	ND<	ND<	ND<	0.6	ND<	ND<	ND<	ND<	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.29	22.0	ND<	4.0	ND<	1.0
	03/12/97	3	6.4	ND<	ND<	ND<	1.4	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	9.0	ND<	ND<	ND<	ND<
MCL1			6.4-10.0	0.2	NL	NL	NL	NL	NL	0.006	0.05	2.0	0.004	0.005	0.1	NL	1.3	0.015	0.002	0.1	0.05	0.05	0.002	NL	NL	5.0	200	5.0	NL	NL
MCL2			6.5-8.5	0.2	NL	NL	NL	NL	NL	NL	0.05	1.0	NL	0.010	0.05	NL	1.0	0.015	0.002	NL	0.01	0.05	NL	NL	NL	NL	NL	NL	NL	NL
MCL3			NL	0.2	NL	NL	NL	NL	0.006	NL	2.0	0.004	0.005	0.1	NL	NL	NL	0.002	0.1	0.05	NL	0.002	NL	NL	5.0	200	5.0	NL	NL

Notes:

1 Well sampled by Con-Test
2 Well sampled by Fuss & O'Neill
3 Well sampled by Aegis, Inc.
NA - Not analyzed
ND< - Below laboratory detection limit
NL - No MCL has been established for this parameter.
<# - Parameter is below alternative laboratory detection of #.
* Well was dry during applicable sampling event and could not be sampled.
** Well damaged in September 1996 and replaced in December 1996.

z - Dissolved Metals detected from 0.05 to 0.18 mg/L
Total Metal and TPH concentrations in milligrams per liter (mg/L)
Volatile Organic Compound concentrations in micrograms per liter (ug/L)
F. Coli - Fecal Coliform concentrations per 100 milliters (/ 100 mL)
TPH - Total Petroleum Hydrocarbon
TOC - Total Organic Carbon
TCE - Trichloroethylene
TCA - 1,1,1-Trichloroethane
PCE - Tetrachloroethene
11DCE - 1,1- Dichloroethane

CFM - Chloroform
11DCA - 1,1-Dichloroethane
T. Cn - Total Cyanide
A. Cn - Amenable Cyanide
MCL1 - Maximum Contaminant Levels of the Connecticut Department of Public Health and Addiction Services Public Drinking Water Quality Regulations.
MCL2 - Maximum Contaminant Levels of the Connecticut Department of Public Health Primary Drinking Water Standards.
MCL3 - Maximum Contaminant Levels of 40 CFR 141.00 Maximum Contaminant Levels for Organic and Inorganic Contaminants.

Aegis, Inc.

TABLE 2

(Sheet 2 of 2)

Historical Ground Water Quality Data

500 South Broad Street, Meriden, Connecticut

Well ID	Sample Event	Foot Note	PARAMETER																									
			pH	T. Cn	A. Cn	TPH	TOC	F. Coli	T. Sb	T. As	T. Ba	T. Be	T. Cd	T. Cr	Cr6	T. Cu	T. Pb	T. Hg	T. Ni	T. Se	T. Ag	T. Tl	T. Sn	T. Zn	TCE	TCA	PCE	11DCA	CFM
MW-12	03/08/95	3	6.8	ND<	ND<	ND<	1.9	ND<	<.05	ND<	0.8	<.1	ND<	0.06	NA	0.09	0.014	ND<	ND<	ND<	ND<	<.5	NA	0.34	1.0	ND<	ND<	ND<	ND<
	06/29/95	3	6.8	ND<	ND<	ND<	2.0	ND<	ND<	ND<	1.5	0.007	ND<	0.20	NA	0.31	0.014	ND<	0.08	ND<	ND<	ND<	ND<	0.65	ND<	ND<	ND<	ND<	ND<
	09/27/95	3	6.8	ND<	ND<	ND<	2.1	ND<	ND<	ND<	2.7	0.012	ND<	0.44	0.12	0.59	0.072	ND<	0.16	ND<	ND<	ND<	ND<	1.13	ND<	ND<	ND<	ND<	ND<
	12/19/95	3	6.7	ND<	ND<	ND<	2.0	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
	03/14/96	3	6.7	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.13	ND<	ND<	ND<	ND<	ND<
	06/13/96	3	6.8	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.17	ND<	ND<	ND<	4.0	ND<
	09/16/96	3	6.8	ND<	ND<	ND<	ND<	ND<	ND<	ND<	1.0	ND<	ND<	0.05	0.05	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.53	ND<	ND<	ND<	ND<	ND<
	03/12/97	3	6.7	ND<	ND<	ND<	1.8	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
MW-13	03/08/95	3	6.4	0.06	ND<	ND<	1.4	ND<	<.05	ND<	0.8	<.1	ND<	0.05	NA	0.10	0.032	ND<	ND<	ND<	ND<	<.5	NA	0.40	2.0	ND<	ND<	ND<	ND<
	06/29/95	3	6.5	ND<	ND<	ND<	1.4	ND<	ND<	ND<	0.5	ND<	ND<	ND<	NA	0.08	0.015	ND<	ND<	ND<	ND<	ND<	ND<	0.29	2.0	1.0	ND<	ND<	ND<
	09/27/95	3	6.6	0.17	ND<	ND<	1.3	ND<	ND<	ND<	ND<	0.010	ND<	0.09	ND<	0.08	0.024	ND<	0.08	ND<	ND<	ND<	ND<	0.13	5.0	ND<	ND<	ND<	ND<
	12/19/95	3	6.3	0.06	ND<	ND<	1.1	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
	03/14/96	3	6.2	ND<	ND<	ND<	1.9	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.12	1.0	ND<	ND<	ND<	ND<
	06/13/96	3	6.1	0.05	ND<	ND<	1.5	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.22	14.0	7.0	ND<	4.0	ND<
	09/16/96	3	6.4	0.23	0.05	ND<	1.5	ND<	ND<	ND<	0.6	ND<	ND<	ND<	ND<	0.01	ND<	ND<	ND<	ND<	ND<	ND<	ND<	0.43	3.0	ND<	ND<	ND<	ND<
	03/12/97	3	6.2	0.09	ND<	ND<	1.6	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<	ND<
MCL1			6.4-10.0	0.2	NL	NL	NL	NL	0.006	0.05	2.0	0.004	0.005	0.1	NL	1.3	0.015	0.002	0.1	0.05	0.05	0.002	NL	NL	5.0	200	5.0	NL	NL
MCL2			6.5-8.5	0.2	NL	NL	NL	NL	NL	0.05	1.0	NL	0.010	0.05	NL	1.0	0.015	0.002	NL	0.01	0.05	NL	NL	NL	NL	NL	NL	NL	NL
MCL3			NL	0.2	NL	NL	NL	NL	0.006	NL	2.0	0.004	0.005	0.1	NL	NL	NL	0.002	0.1	0.05	NL	0.002	NL	NL	5.0	200	5.0	NL	NL

Notes:

1 Well sampled by Con-Test
2 Well sampled by Fuss & O'Neill
3 Well sampled by Aegis, Inc.
NA - Not analyzed
ND< - Not Detected
NL - No MCL has been established for this parameter.
<# - Parameter is below alternative laboratory detection of #.
z - Dissolved Metals detected from 0.05 to 0.18 mg/L
Total Metal and TPH concentrations in milligrams per liter (mg/L)
Volatile Organic Compound concentrations in micrograms per liter (ug/L)
F. Coli - Fecal Coliform concentrations per 100 milliliters (/ 100 mL)
TPH - Total Petroleum Hydrocarbon
TOC - Total Organic Carbon
TCE - Trichloroethylene
TCA - 1,1,1-Trichloroethane
PCE - Tetrachloroethene
11DCE - 1,1- Dichloroethane
CFM - Chloroform
11DCA - 1,1-Dichloroethane
T. Cn - Total Cyanide
A. Cn - Amenable Cyanide
MCL1 - Maximum Contaminant Levels of the Connecticut Department of Public Health and Addiction Services Public Drinking Water Quality Regulations.
MCL2 - Maximum Contaminant Levels of the Connecticut Department of Public Health Primary Drinking Water Standards.
MCL3 - Maximum Contaminant Levels of 40 CFR 141.00 Maximum Contaminant Levels for Organic and Inorganic Contaminants.

TABLE 3

(Sheet 1 of 2)

Historical Ground Water Field Measurement Data

500 South Broad Street, Meriden, Connecticut

Well ID	Monitoring Event	Ground Water Temperature (Celsius)	Specific Conductance (MicroSeimens/cm)	pH	Dissolved Oxygen (ppm)
MW-1	03/08/95	10.1	201	5.5	—
	06/29/95	*	*	*	*
	09/27/95	*	*	*	*
	12/19/95	8.8	308	6.4	—
	03/14/96	7.6	181	5.8	9.9
	06/13/96	11.1	301	5.8	7.2
	09/19/96	**	**	**	**
MW-1(R)	03/13/97	8.9	488	6.1	6.3
MW-4	03/08/95	6.5	870	6.0	—
	06/29/95	12.9	578	6.2	13.3
	09/27/95	*	*	*	*
	12/19/95	7.5	693	6.6	—
	03/14/96	6.2	687	6.5	10.8
	06/13/96	11.5	452	6.4	6.6
	09/19/96	14.0	505	6.4	5.3
	03/13/97	5.6	400	6.7	8.1
MW-8	03/08/95	11.8	674	6.1	—
	06/29/95	12.9	702	6.5	10.8
	09/27/95	14.9	597	7.1	10.3
	12/19/95	12.3	498	6.5	—
	03/14/96	11.8	486	6.2	10.4
	06/13/96	12.3	548	5.9	6.0
	09/19/96	13.3	737	6.4	5.0
	03/13/97	11.3	550	6.0	7.8

Notes: * - Data not collected due to dry conditions.

** - Monitor well MW-1 was damaged in September 1996.

'— Dissolved oxygen was not measured in March 1995 and December 1995.

Data represents average of three sets of measurements collected.

ppm - parts per million

cm - centimeter

TABLE 3

(Sheet 2 of 2)

Historical Ground Water Field Measurement Data

500 South Broad Street, Meriden, Connecticut

Well ID	Monitoring Event	Ground Water Temperature (Celsius)	Specific Conductance (MicroSeimens/cm)	pH	Dissolved Oxygen (ppm)
MW-12	03/08/95	11.6	452	6.5	—
	06/29/95	12.9	436	6.4	13.1
	09/27/95	14.0	462	6.7	4.4
	12/19/95	11.1	340	6.7	—
	03/14/96	11.1	402	6.6	7.8
	06/13/96	11.6	324	6.6	6.4
	09/19/96	12.7	443	6.2	5.4
	03/13/97	10.3	307	6.6	6.4
MW-13	03/08/95	12.6	651	6.6	—
	06/29/95	13.0	504	6.1	9.3
	09/27/95	14.8	509	6.5	9.8
	12/19/95	11.4	368	6.1	—
	03/14/96	12.3	442	6.2	5.2
	06/13/96	12.2	392	5.9	4.3
	09/19/96	13.5	472	5.9	4.0
	03/13/97	11.7	387	6.0	6.6

Notes: * - Data not collected due to dry conditions.
** - Monitor well MW-1 was damaged in September 1996.
'— Dissolved oxygen was not measured in March 1995 and December 1995.
Data represents average of three sets of measurements collected.
ppm - parts per million
cm - centimeter

APPENDIX C

MONITOR WELL BORING LOGS AND WELL COMPLETION REPORTS

APPENDIX C

C.E. PRATT & SON
Sheep Pasture Rd. Southwick, Ma.
(413) 569-5671

CLIENT: Con-Test

SHEET 1 OF 6
HOLE NO. 1

DRILLER: S. Warner
INSPECTOR: A. Desrosiers

PROJECT NAME: Devcon
LOCATION: 500 So. Broad St., Meriden, Ct.

Job No. 7836
Dig Safe No. 89120161

GROUND WATER OBSERVATIONS
____ FT. AFTER ____ HOURS
AT ____ FT. AFTER ____ HOURS

	CASING	SAMPLER	CORE BARREL
TYPE	PVC	s/s	
SIZE I.D.	2"		
HAMMER WT.	140#		
HAMMER FALL	30"		

DATE START 3/29/88 DATE FIN. 3/30/8
SURFACE ELEV.
GROUND WATER ELEV.

A	STRATUM DESCRIPTION	BLOWS PER 6"	B
5	Sandy Loam	3-5-5	
10	Till	11-24-20	
12	Wet		
15	Till/Ledge	50=4"	
16	Refusal		
	10' Screen #10 Slot		

A	STRATUM DESCRIPTION	BLOWS PER	B

FIGURE 2

con-test

WATER AND AIR ENGINEERING

P.O. BOX 591
EAST LONGMEADOW
MASSACHUSETTS 01028
(413)525-1198

AS-BUILT WELL DIAGRAM & GEOLOGIC DESCRIPTION

WELL NO. 1 PROJECT NO. 7836

CLIENT: DEVCON
PRJ. NAME: INTERNATIONAL SILVER
LOCATION: 600 SOUTH BROAD STREET
MERIDAN, CONN.
GEOLOGIST: ALAN DeROSIERS
DATE OF DRILL: 3/28/89

BORING SIZE: 6"
CASING TYPE: PVC
CASING ID: SCHEDULE 40
TYPE OF FILTER PACK: NEW JERSEY SAND

GROUND WATER OBSERVATION
11.26 FT ON 4/4/89 DATE
MEASURED FROM WELL CASING
@ ELEVATION 106.76 = GROUND
WATER ELEVATION 95.50

DRAWN BY ANNE DeSELLIER
DATE 4/10/89
APPROVED BY
DATE



SAMPLE NO. AND DESCRIPTION

7836-01 4.5-5.5'
LOAM AND SANDY LOAM

7836-02 9.5-10.5'
MEDIUM SAND AND TILL

7836-03 14.5-15.5'
TILL AND LEDGE

TOTAL WELL DEPTH = 15'

AEGIS, INC.
Environmental Consultants
2138 Silas Deane Highway
Rocky Hill, CT 06067-2315
Tel. 860-563-1041

Hole No.: MW-1(R)
Offset: —

Well Location Map



Client: Silver Hill Business Center **Site Location:** Front of Pep Boy's nr curb in parking l
Address: 500 South Broad St. **Address:** 500 South Broad Street

Project #:

	Casing	Sampler	Core Bar.
Type		NA	
Size ID			
Hammer Wt.			Bit
Hammer Fall			

Date Started: 12/6/96
Date Compl.: 12/6/96
Boring Foreman: Sima Drilling
Insp./Soil Engr.: Aegis, Inc.

Ground Water Observations
At: ~12' After: 0 Hours
At: After: Hours

Sample Depths (ft)	Casing Blows per foot	Type Of Sample	Blow-Counts	Moisture Density or Consist.	Strata Change Elev.	SOIL IDENTIFICATION	GasTech Reading (ppm)	Sample No	Sample Pen	Sample Rec
0-0.5						0.5 feet of asphalt				
0.5-17		cuttings		wet		Red brown very fine sand, some clay, little coarse sand and silt. Sand appears to be from screen pack. PVC fragments evident.		—	—	—
17-18		cuttings		wet		Red brown very fine sand, some clay, little silt. Drilling became much difficult at 17 feet (drop pressure from 300 to 500 psi), very difficult at 18 feet.		—	—	—
						Bottom of boring 18 feet.				
						Set 10 feet (10 slot) PVC screen				
						8 feet PVC risers.				
						3.0 bags sand (100 lbs)				
						1.5 bag bentonite (50 lbs)				
						2.0 bags concrete (50 lbs)				
						1 road box and plug.				

Ground surface to 18' used PVC casing then Set well at 18' w/ 10 feet screen.

Sample Type
D=dry C=cored W=washed
UP=undisturbed piston
A=auger V=vane test
SS=split spoon
UT=undisturbed thinwall

Proportions used
Trace 0-10%
Little 10-20%
Some 20-35%
And 35-50%

Cohesionless Density
Loose 0-10
M/Dense 10-30
Dense 30-50
V. Dense 50+

Cohesive Consistency
Soft 0-4
M/Stiff 4-8
Stiff 8-15
V. Stiff 15-30
Hard 30+

Summary
Boring: 18 feet
Coring: —
No. of Samples —

SIMA DRILLING COMPANY 150 SCHOOL HOUSE ROAD CHESHIRE CT 06410	FIELD REP. SCOTT CONTRACTOR: AEGIS INC. DRILLER: DOMENIC BRIGLIA	PROJECT: SILVER HILL DATE: DECEMBER 6, 1996

BORING # MW-1(R)
METHOD: AUGER
DIAMETER: 4 1/4"
TOTAL DEPTH: 18'

BORING LOCATION:
500 SOUTH BROAD STREET
MERIDEN, CT

Pg: 1 of: 1

D	X	Sam No.	0 6"	6" 12"	12" 18"	18" 24"	rec	Sample Description	Strat Chg	General Description	Well Detail	D
0											GG 2" GG	0
											GG GG	
											GG R GG	
											GG I GG	
											\\\\ S \\\\	
5											\\\\ E \\\\	5
											\\\\ R \\\\	
											::::: :::::	
											::::: :::::	
											::::: == :::::	
10											::::: == :::::	10
											::::: == :::::	
											::::: == :::::	
											::::: == :::::	
											::::: == :::::	
15											::::: == :::::	15
											::::: == :::::	
17'								17' END OF OLD HOLE, DRILLED			::::: == :::::	
								TO 18'-HARDPAN			::::: == :::::	

20												20
25												25
30												30
35												35
40												40
45												45

MATERIALS USED		size /type	quantity	MATERIALS USED		size/type	quantity
WELL SCREEN	==	2" P.V.C.	10'	WELL PROTECTOR		8" FLUSH	1
SLOT SIZE		10 SLOT		GROUT	GG		
RISER PIPE		2" P.V.C.	10'	BACKFILL	BB	CEMENT	
GRADED SAND	::::::	#1 MORIE	300 LBS.	STEAM CLEANER		YES	
BENTONITE	\\\\	HOLEPLUG	75 LBS.	TIME: DECEMBER 6, 1996		8:00-11:00	

NOTES:

BORING CONTRACTOR: Sima Drilling Co.

WELL MW-1(R)

MONITOR WELL CONSTRUCTION DETAIL

UNCONSOLIDATED MATERIAL

SHEET 1 OF 1

PROJ # 1835050A

LOG PREPARED BY:

CONTR. ____ AEGIS X



AEGIS Inc.
2139 Silas Deane Highway
Rocky Hill CT 06067-2315
Tel (203) 563-0141
FAX (203) 529-5124
Environmental Consultants

PROJECT NO.	1835050A
DATE :	12/6/96
SCALE :	NOT TO SCALE
DRAWN BY :	J.C.J.
DWG NO.	G61 MWWELLFM
CLIENT	Pep Boy's
PROJECT	Well Location : 500 South
DRAWING TITLE	Broad St. Meriden CT

MW-1(R)

APPENDIX C

C.E. PRATT & SON
Sheep Pasture Rd. Southwick, Ma.
(413) 569-5671

CLIENT: Con-Test

SHEET 4 OF 6
HOLE NO. 4

ILLER: S. Warner
PECTOR: A. Desrosiers

PROJECT NAME: Devcon
LOCATION: 500 So. Broad St., Meriden, Ct.

DESIGNATION Job No. 7836
ACCESS Dig Safe No. 89120161

GROUND WATER OBSERVATIONS
____ FT. AFTER ____ HOURS
AT ____ FT. AFTER ____ HOURS

	CASING	SAMPLER	CORE BARREL
TYPE	PVC	s/s	
SIZE I.D.	2"		
HAMMER WT.	140		
HAMMER FALL	30"		

DATE START 3/29/88 DATE IN 3/30/8:
SURFACE ELEV. ____
GROUND WATER ELEV. ____

A	STRATUM DESCRIPTION	BLOWS PER 6	B
5	Clay	10-16-10	
	Wet		
10	Till	8-7-8	
15	Till/Clay	9-19-21	
	10' Screen #10 Slot		

A	STRATUM DESCRIPTION	BLOWS PER	B

FIGURE 2

con-test
WATER AND AIR ENGINEERING
P.O. BOX 591
EAST LONGMEADOW
MASSACHUSETTS 01028
(413)525-1198

AS-BUILT WELL DIAGRAM & GEOLOGIC DESCRIPTION

WELL NO. 4 PROJECT NO. 7836

CLIENT: DEVCON
PRJ. NAME: INTERNATIONAL SILVER
LOCATION: 500 SOUTH BROAD STREET
MERIDAN, CONN.
GEOLOGIST: ALAN DeROSIERS
DATE OF DRILL: 3/30/89

BORING SIZE: 6"
CASING TYPE: PVC
CASING ID: SCHEDULE 40
TYPE OF FILTER PACK: NEW JERSEY SAND

GROUND WATER OBSERVATION
3.60 FT ON 4/4/89 DATE
MEASURED FROM WELL CASING
R ELEVATION 74.27 = GROUND
WATER ELEVATION 70.67

DRAWN BY ANNE DeSELLIER
DATE 4/10/89
APPROVED BY
DATE



SAMPLE NO. AND DESCRIPTION

7836-12 4.5-5.5'
CLAY

7836-13 9.5-10.5'
CLAY - TILL

7836-14 14.5-15.5'
CLAY - TILL

TOTAL WELL DEPTH = 15'

FUSS & O'NEILL, INC.
CONSULTING ENGINEERS
MANCHESTER, CT 06040

PROJECT/LOCATION: OFUCON, Meriden, CT

BORING NO. MW-8
SHEET 1 OF 2
JOB. NO. 92-238

DRILLING CO. Associated Drilling Co.
DRILLER [illegible]
FUSS & O'NEILL REPRESENTATIVE JMB

BORING LOCATION
GROUND ELEVATION
DATE STARTED 12-16-92 DATE FINISHED 12-16-92

DRILLING METHOD HSA 4¼" ID
SAMPLING METHOD Split Spoon
HAMMER WT. 140 HAMMER FALL (IN) 30

WATER LEVEL MEASUREMENTS

DATE	MS. PT.	WATER AT	HR AFTER COMPLETION
12-16-92	EYC	18'	

DEPTH (ft)	CASING	SAMPLE NO.	DEPTH (ft)	PEN/REC.	BLOWS/6"	SOIL DENSITY	SAMPLE DESCRIPTION	USCS	FIELD TESTING	DEPTH (ft)
1										
2		S-1	-4	/16	5-6 3-4	Loose	(2-3.5) Sand [illegible] asphalt, [illegible] moist	—	1 ppm	
		S-2		/0	[illegible] 2-6	Loose	No Recovery	—	—	
		S-3		/16	2-2 3-5	Loose	(6-6.5) Sand f-c, Trace [illegible] S, Grayish Red 10R 4/2, moist	SP	0	
		S-4		/24	3-5 5-7	Medium	(8-10) Sand, Fine, trace [illegible] [illegible]	SP	0	
		S-5		24/	4-4 6-9	[illegible]	(10-11) Sand, F-M, [illegible] [illegible] 5YR [illegible]	SP	200 ppm	
		S-6		24/	15-15 15-15	[illegible]	[illegible] Sand, Fm, Grayish Red 10R 4/2, [illegible]	SP	800 ppm	
12										
		S-7		24/	16-22 34-23	medium	(14-15.5) Sand, Fine, little silt, Trace [illegible] gravel, [illegible]	SP-SM	10 ppm	

PROPORTIONS USED	BORING METHOD	DEPTH
TRACE 0 TO 10%	HSA	20'
LITTLE 10 TO 20%		
SOME 20 TO 35%		
AND 35 TO 50%		

REMARKS:
FIELD INSTRUMENT: [illegible]

NOTE: Geologic Log Based on Procedures Described in ASTM Standard D 2488.

BORING NO. MW-8

WELL NO. mw-8



WELL CONSTRUCTION DETAILS

mw-8

PROJ. NO. 92-228 DATE: SCALE: N.T.

SIMA DRILLING COMPANY
150 SCHOOL HOUSE ROAD
CHESHIRE CT 06410

FIELD REP. JEFF JENKINS
CONTRACTOR: AEGIS INC.
DRILLER: DOMENIC BRIGLIA

PROJECT: SILVER HILL
DATE: FEBRUARY 20, 1995

BORING # MW12
METHOD: AUGER
DIAMETER: 4 1/4"
TOTAL DEPTH: 25'

BORING LOCATION:
500 SOUTH BROAD STREET
MERIDEN, CT

Pg: 1 of: 1

D	X	Sam No.	0 6"	6" 12"	12" 18"	18" 24"	rec	Sample Description	Strat Chg	General Description	Well Detail	D
0	X		9	4	3	5		FILL, MEDIUM SAND & ROCKS			BB 2" BB	0
2											BB BB	
2	X		8	15	22	50		FILL, MEDIUM SAND & ROCKS			BB P BB	
4								AUGER REFUSAL @ 3'6" MOVED 4" BACK.			BB V BB	
4	X		11	9	15	11		TIGHT FINE SAND, SOME ROCKS			BB C BB	
6											BB BB	5
6	X		6	4	4	3		TIGHT FINE SAND			BB R BB	
8											BB I BB	
8	X		2	3	4	6		FINE SAND			BB S BB	
10											BB E BB	
10	X		2	2	1	3		FINE SAND TO A SILTY SAND			\\\\ R \\\\	10
12											\\\\ \\\\	
12	X		7	7	8	10		FINE TIGHT REDISH COLOR SAND			\\\\ \\\\	
14											::::: :::::	
14	X		10	12	11	15		FINE SAND DAMP TO 16'.			::::: :::::	
16											::::: == :::::	15
16	X		28	35	32	36		FINE SAND & ROCKS.			::::: == :::::	
18									17'6"	WET?	::::: == :::::	
18	X		13	15	14	23		MEDIUM SAND, WET AT 19'.			::::: == :::::	
20											::::: == :::::	
20	X		18	29	50	----		MEDIUM SAND & ROCKS			::::: == :::::	20
22											::::: == :::::	
22	X		50	FOR	4"			MEDIUM SAND, LOOKS LIKE TILL			::::: == :::::	
24											::::: == :::::	
24	X		29	50	---	---		(SAME AS ABOVE)			::::: == :::::	
26											::::: == :::::	25
30												30
35												35
40												40
45												45

MATERIALS USED		size /type	quantity
WELL SCREEN	==	2" STAINL	10'
SLOT SIZE		0.1	
RISER PIPE		2" P.V.C.	20'
GRADED SAND	::::::	#1 MORIE	325 LBS.
BENTONITE	\\\\\	HOLEPLUG	50 LBS.

MATERIALS USED		size/type	quantity
WELL PROTECTOR		4" STICKUP	1
GROUT	GG		
BACKFILL	BB	YES	
STEAM CLEANER		YES	
TIME: FEBRUARY 20, 1995		7:45--4:30	

NOTES:

BORING CONTRACTOR
Sima Drilling
Cheshire, CT

Dominic Sima
and Shane Sima

WELL MW-12

MONITOR WELL CONSTRUCTION DETAIL

UNCONSOLIDATED MATERIAL

SHEET 1 OF 1

PROJ # 0307050C

LOG PREPARED BY:

CONTR. ____ AEGIS PS



AEGIS Inc.
2139 Silas Deane Highway
Rocky Hill, CT 06067-2315
Tel. (203) 563-8141
FAX (203) 529-5124
Environmental Consultants

PROJECT NO. 0307050C	CLIENT 500 S. Broad
DATE: 2-20-95	PROJECT Meriden, CT
SCALE: NOT TO SCALE	
DRAWN BY: J.C.J.	
DWG NO. 681 MWWELL.FH	DRAWING TITLE

MW-12

WELL COMPLETION REPORT

CPE-9 REV. 11-82

STATE OF CONNECTICUT
DEPARTMENT OF CONSUMER PROTECTION
WELL DRILLING BOARD
165 CAPITOL AVE.
HARTFORD, CONNECTICUT 06106

Do NOT fill in
STATE WELL NO
OTHER NO

OWNER — NAME: Silver Hill Business Center C/O AEGIS Inc. — ADDRESS: 2138 Silas Deane Highway Rocky

LOCATION OF WELL — (No. & Street): 500 South Broad Street — (Town): Meriden — (Lot Number): MW12

PROPOSED USE OF WELL
- [ ] DOMESTIC
- [ ] BUSINESS ESTABLISHMENT
- [ ] FARM
- [ ] TEST WELL
- [ ] PUBLIC SUPPLY
- [ ] INDUSTRIAL
- [ ] AIR CONDITIONING
- [X] OTHER (Specify) Monitor Well

DRILLING EQUIPMENT
- [ ] ROTARY
- [ ] COMPRESSED AIR PERCUSSION
- [ ] CABLE PERCUSSION
- [X] OTHER (Specify) Auger

CASING DETAILS — LENGTH (feet): 15' — DIAMETER (inches): 2" PVC — WEIGHT PER FOOT: Sch 40
- [X] THREADED [ ] WELDED
- DRIVE SHOE: [ ] YES [X] NO
- WAS CASING GROUTED? [X] YES [ ] NO

YIELD TEST
- [ ] BAILED [ ] PUMPED [ ] COMPRESSED AIR
- HOURS:
- YIELD (G.P.M.): N/A

WATER LEVEL — MEASURE FROM LAND SURFACE—STATIC (Specify feet): — DURING YIELD TEST (feet): — Depth of Completed Well in feet below Land surface.: 25'

SCREEN DETAILS — MAKE: Johnson Stainless — LENGTH OPEN TO AQUIFER (feet): 10'

SLOT SIZE	DIAMETER (inches)	IF GRAVEL PACKED:	Diameter of well including gravel pack (inches)	GRAVEL SIZE (inches)	FROM (feet)	TO (feet)
.010	2"			#1 Morie	12'	25'

DEPTH FROM LAND SURFACE FEET TO FEET		FORMATION DESCRIPTION
0	18	Fine Sand
18	25	Medium Sand

Sketch exact location of well with distances, to at least two permanent landmarks.



If yield was tested at different depths during drilling, list below

FEET	GALLONS PER MINUTE

DATE WELL COMPLETED	PERMIT NO.	REGISTRATION NO.	DATE OF REPORT	WELL DRILLER (Specify)
2/20/95	168179	W3-4	2/22/95	Sims Drilling

OWNER

SIMA DRILLING COMPANY
150 SCHOOL HOUSE ROAD
CHESHIRE CT 06410

FIELD REP. JEFF JENKINS
CONTRACTOR: AEGIS INC.
DRILLER: DOMENIC BRIGLIA

PROJECT: SILVER HILL
DATE: FEBRUARY 20, 1995

BORING # MW13
METHOD: AUGER
DIAMETER: 4 1/4"
TOTAL DEPTH: 25'

BORING LOCATION:
500 SOUTH BROAD STREET
MERIDEN, CT

Pg: 1 of: 1

D	X	Sam No.	0 6"	6" 12"	12" 18"	18" 24"	rec	Sample Description	Strat Chg	General Description	Well Detail	D
0	X		1	2	2	2		FINE SAND, LITTLE SILTY RED COLOR, COBBLE 3'--4'6".			BB 2" BB	0
2											BB BB	
											BB P BB	
											BB V BB	
5	X		23	18	12	8		FINE SAND AND MEDIUM GRAVEL MIXED.			BB C BB	
7											BB BB	5
											BB R BB	
											BB I BB	
											BB S BB	
10	X		8	3	2	5		FINE SAND, WET @ 11'.			BB E BB	
12											\\\\ R \\\\	10
											\\\\ \\\\	
											\\\\ \\\\	
											....	
15	X		9	12	12	15		FINE SAND AND MEDIUM GRAVEL.			....	15
17											..... ==	
											..... ==	
											..... ==	
20	X		18	29	35	47		MEDIUM SAND AND ROCKS.			..... ==	
22											..... ==	20
											..... ==	
											..... ==	
											..... ==	
24	X		39	50	---	---		TILL			..... ==	
26											..... ==	25
30												
												30
35												
												35
40												
												40
45												45

MATERIALS USED		size /type	quantity
WELL SCREEN	==	2" STAINL	10'
SLOT SIZE		0.1	
RISER PIPE		2" P.V.C.	20'
GRADED SAND	::::::	#1 MORIE	325 LBS.
BENTONITE	\\\\\	HOLEPLUG	50 LBS.

MATERIALS USED		size/type	quantity
WELL PROTECTOR		4" STICKUP	1
GROUT	GG		
BACKFILL	BB	YES	
STEAM CLEANER		YES	
TIME: FEBRUARY 20, 1995		7:45--4:30	

NOTES:

BORING CONTRACTOR
Sima Drilling
Cheshire, CT
Dominic and Steve Sima

WELL MW-13

MONITOR WELL CONSTRUCTION DETAIL

UNCONSOLIDATED MATERIAL

SHEET 1 OF 1
PROJ # 03071501
LOG PREPARED BY:
CONTR. ____ AEGIS RJ



AEGIS Inc.
2138 Silas Deane Highway
Rocky Hill, CT 06067-2315
Tel (203) 563-1814
FAX (203) 529-5124
Environmental Consultants

PROJECT NO.	03071501
DATE:	2-20-95
SCALE:	NOT TO SCALE
DRAWN BY:	J.C.J.
DWG NO.	G61 MWWELLFM
CLIENT	500 S. Broad St.
PROJECT	Meriden, CT
DRAWING TITLE	

MW-13

WELL COMPLETION REPORT

CPE-9 REV. 11-82

STATE OF CONNECTICUT
DEPARTMENT OF CONSUMER PROTECTION
WELL DRILLING BOARD
165 CAPITOL AVE.
HARTFORD, CONNECTICUT 06106

Do NOT fill in
STATE WELL NO
OTHER NO

OWNER — NAME: Silver Hill Business Center C/O AEGIS Inc. 2138 Silas Deane Highway Rocky — ADDRESS

LOCATION OF WELL — (No. & Street): 500 South Broad Street — (Town): Heriden — (Lot Number): MW13

PROPOSED USE OF WELL — ☐ DOMESTIC ☐ BUSINESS ESTABLISHMENT ☐ FARM ☐ TEST WELL ☐ PUBLIC SUPPLY ☐ INDUSTRIAL ☐ AIR CONDITIONING ☒ OTHER (Specify) Monitor Well

DRILLING EQUIPMENT — ☐ ROTARY ☐ COMPRESSED AIR PERCUSSION ☐ CABLE PERCUSSION ☒ OTHER (Specify) Auger

CASING DETAILS — LENGTH (feet): 15' — DIAMETER (inches): 2" P.V.C. — WEIGHT PER FOOT: Sch 40 — ☒ THREADED ☐ WELDED — DRIVE SHOE ☐ YES ☒ NO — WAS CASING GROUTED? ☒ YES ☐ NO

YIELD TEST — ☐ BAILED ☐ PUMPED ☐ COMPRESSED AIR — HOURS: — YIELD (G.P.M.): N/A

WATER LEVEL — MEASURE FROM LAND SURFACE—STATIC (Specify feet): — DURING YIELD TEST (feet): — Depth of Completed Well in feet below Land surface.: 25'

SCREEN DETAILS — MAKE: Johnson Stainless — LENGTH OPEN TO AQUIFER (feet): 10'

SLOT SIZE	DIAMETER (inches)	IF GRAVEL PACKED	Diameter of well including gravel pack (inches)	GRAVEL SIZE (inches)	FROM (feet)	TO (feet)
.010	2"			#1 Morie	12'	25'

DEPTH FROM LAND SURFACE FEET TO FEET		FORMATION DESCRIPTION
0	12	Fine Sand
12	17	Fine Sand Then Medium Gravel
17	25	Medium Sand to Till.

Sketch exact location of well with distances, to at least two permanent landmarks.



YM

MAIN Complex

PARKING

SOUTH BROAD STREET

If yield was tested at different depths during drilling, list below

FEET	GALLONS PER MINUTE

DATE WELL COMPLETED	PERMIT NO.	REGISTRATION NO.	DATE OF REPORT	WELL DRILLER (Signature)
2/20/95	168179	W3-4	2/22/95	Sima Drilling

OWNER

APPENDIX D

MARCH 1997 LABORATORY ANALYTICAL REPORTS AND CHAINS-OF-CUSTODY

South Broad

April 1, 1997

Aegis, Inc.
2138 Silas Deane Highway
Rocky Hill, CT 06067-2315

Attn: Mr. Mike Zaliznock

Please find attached laboratory report(s) for the samples submitted on : **March 13, 1997**

All pertinent information for this analysis is located on the report. Should it be necessary to contact us regarding billing and or the test results, please have the following information readily available :

LAB No.	: 397192
PO/JOB No.	: 0307050L
INVOICE No.	: 64787
ORDER No.	: 44921
CUSTOMER No.	: 107

Please feel free to contact us if you have any questions.

Very truly yours,

Stephen J. Franco
Laboratory Director
PH-0547

RECEIVED
APR 4 1997
AEGIS, INC.

connecticut testing laboratories inc.
WATER ■ SOIL ■ AIR

STEPHEN J. FRANCO
Laboratory Director
PHONE ■ 203/634-3731
165 GRACEY AVENUE ■ MERIDEN, CT ■ 06451

Date Samples Received : 3-13-97

Client Name: **Aegis Environmental**	CTL Lab. No.397192
Report Date: 4-1-97	PO/Job No. 0307050L

RESULTS OF ANALYSIS

Matrix Type	W	W	W	W
CTL Sample No.	2876	2877	2878	2879
Field Id	MW-1(R)	MW-4	MW-8	MW-12
Arsenic-mg/L	ND<0.05	ND<0.05	ND<0.05	ND<0.05
Silver-mg/L	ND<0.01	ND<0.01	ND<0.01	ND<0.01
Beryllium-mg/L	ND<0.004	ND<0.004	ND<0.004	ND<0.004
Cadmium-mg/L	ND<0.005	ND<0.005	ND<0.005	ND<0.005
Chromium, Total-mg/L	ND<0.05	ND<0.05	ND<0.05	ND<0.05
Copper-mg/L	ND<0.01	ND<0.01	ND<0.01	ND<0.01
Lead-mg/L	ND<0.010	ND<0.010	ND<0.010	ND<0.010
Mercury-mg/L	ND<0.002	ND<0.002	ND<0.002	ND<0.002
Nickel-mg/L	ND<0.05	ND<0.05	ND<0.05	ND<0.05
Selenium-mg/L	ND<0.01	ND<0.01	ND<0.01	ND<0.01
Antimony-mg/L	ND<0.006	ND<0.006	ND<0.006	ND<0.006
Thallium-mg/L	ND<0.002	ND<0.002	ND<0.002	ND<0.002
Zinc-mg/L	ND<0.05	ND<0.05	ND<0.05	ND<0.05
Barium-mg/L	ND<0.5	ND<0.5	ND<0.5	ND<0.5
Tin-mg/L	ND<0.5	ND<0.5	ND<0.5	ND<0.5
Chromium, Hexavalent-mg/L	ND<0.05	ND<0.05	ND<0.05	ND<0.05
Cyanide, Amenable-mg/L	ND<0.05	ND<0.05	ND<0.05	ND<0.05
Cyanide, Total-mg/L	ND<0.05	ND<0.05	ND<0.05	ND<0.05
pH	6.0	6.6	6.4	6.7
Oil & Grease(TPH)-mg/L	ND<5	ND<5	ND<5	ND<5
TOC-mg/L	1.4	2.6	1.4	1.8
Fecal Coliform/100ml	ND<10	ND<10	ND<10	ND<10

Matrix Types : W = Water/Aqueous
S = Soil/Solid
O = Oil/Hydrocarbons

CONNECTICUT TESTING LABORATORIES, INC.
165 Gracey Avenue / Meriden, CT 06451-2268
(203)-634-3731
Connecticut Certification No. PH-0547

Date Samples Received : 3-13-97

Client Name: **Aegis Environmental**	CTL Lab. No.397192
Report Date: 4-1-97	PO/Job No. 0307050L

RESULTS OF ANALYSIS

Matrix Type	**W**			
CTL Sample No.	**2880**			
Field Id	**MW-13**			
Arsenic-mg/L	ND<0.05			
Silver-mg/L	ND<0.01			
Beryllium-mg/L	ND<0.004			
Cadmium-mg/L	ND<0.005			
Chromium, Total-mg/L	ND<0.05			
Copper-mg/L	ND<0.01			
Lead-mg/L	ND<0.010			
Mercury-mg/L	ND<0.002			
Nickel-mg/L	ND<0.05			
Selenium-mg/L	ND<0.01			
Antimony-mg/L	ND<0.006			
Thallium-mg/L	ND<0.002			
Zinc-mg/L	ND<0.05			
Barium-mg/L	ND<0.5			
Tin-mg/L	ND<0.5			
Chromium, Hexavalent-mg/L	ND<0.05			
Cyanide, Amenable-mg/L	ND<0.05			
Cyanide, Total-mg/L	0.09			
pH	6.2			
Oil & Grease(TPH)-mg/L	ND<5			
TOC-mg/L	1.6			
Fecal Coliform/100ml	ND<10			

Matrix Types : W = Water/Aqueous
S = Soil/Solid
O = Oil/Hydrocarbons

CONNECTICUT TESTING LABORATORIES, INC.
165 Gracey Avenue / Meriden, CT 06451-2268
(203)-634-3731
Connecticut Certification No. PH-0547

CHAIN OF CUSTODY No. 18381

CONNECTICUT TESTING LABORATORIES, INC.
165 Gracey Avenue / Meriden, CT 06451
Tel # 203-634-3731 Fax # 203-630-1336

Client Name : SOUTH BROAD STREET ASSOCIATES 500 S. BROAD ST. MERIDEN, CT
Send Report To : AEGIS, INC.
Send Bill To : AEGIS, INC. PO#: 9370501
QUOTE: SFAAE637.QTE

Samples Collected By (Print) JEFF JENKINS
Signature : [signature]

☒ STANDARD (10 Working Days)
☐ PRIORITY (See Fee Schedule)
☒ ALL Analysis ☐ Metals Only ☐ Organics Only

LAB USE ONLY... 397192 **FILE COPY**

#	Field Identifications (PLEASE PRINT NEATLY)	TIME	DATE SAMPLED	SAMPLE MATRIX W, S, O	BOTTLE TYPE P, G, V	PRESERV. USED A, B, C, N	SAMPLE VOLUMES	
1	MW-1(R)	0735	3-13-97	W	P, G, V	A, B, C	1L (2)	P
2	MW-4	1055	"	"	"	"	500mL (1)	P
3	MW-8	1525	"	"	"	"	500mL (1)	G
4	MW-12	1250	"	"	"	"	4oz (1)	P
5	MW-13	1410	"	"	"	"	40mL (2)	V
6								
7	*NOTE: please report Antimony, Lead, Cadmium, Thallium							
8	Beryllium MCL's according to current FEDERAL REGISTER							

ANALYSIS...	1	2	3	4	5	6	7	8	NOTES
METALS, DISS. WTR-8									
METALS, TOTAL WTR-8									
METALS, TOTAL SOIL-8									
EPTOX METALS S/(W)	X	X	X	X	X				13 TOTAL
TCLP METALS S/W									
TCLP VOLATILES - 11									
TCLP SEMI VOL. - 13									
TCLP PEST/HERB - 8									
TCLP COMPLETE - 40									
601/8010 SCAN									
602/8020 SCAN									
8015 SCAN									
8240 SCAN									
624 SCAN									
625 SCAN									
604 SCAN									
608/8080 FULL SCAN									
608/8080 PCB ONLY									
8260 SCAN									
8100 (PAH) SCAN									
TOC	X	X	X	X	X				
TOX									
Pb % (PAINT CHIPS)									
WATER POTABILITY									
EDB SCAN									
COLIFORM BACTERIA	X	X	X	X	X				FECAL

ANALYSIS...	1	2	3	4	5	6	7	8	NOTES
pH / SPEC COND.	X	X	X	X	X				
COPPER / NICKEL									
TSS / TDS									
NITRATE-N / NITRITE-N									
CN - TOT. / CN - AMEN.									
BOD (5) (20) / COD									
AMMONIA - N / TKN									
TPH - EPA 418.1	X	X	X	X	X				
OIL & GR. EPA 413.2									
FILTER SAMPLES									
PRESERVE SAMPLES									
EXTRA PARAMETERS - PLEASE LIST SEPARATELY									
BARIUM	X	X	X	X	X				
TIN	X	X	X	X	X				
T. CYANIDE	X	X	X	X	X				
A. CYANIDE	X	X	X	X	X				
Cr6	X	X	X	X	X				

RELINQ BY: [signature]	Date 3/13/97 Time 1615	RELINQ BY:	Date Time
REC'D BY: Maureen McMahon	Date 3/13/97 Time 4:15	REC'D BY:	Date Time

Please fill in the Field ID's exactly as they appear on the bottle labels. All used samples are kept refrigerated for 45 days from Date Received unless otherwise instructed. The number after the analyte refers to the number of tests associated with that parameter. Where there are more than one item per line, please circle the desired test(s).

MATRICES W = WATER S = SOIL O = OIL / HYDROCARBON   PRESERVATIONS A = ACID B = BASE C = COOL N = NONE

ORIGINAL

AEGIS, INC.

Environmental Laboratory Services

2138 Silas Deane Highway * Rocky Hill * CT * Tel: (860)563-1041 * Fax: (860)529-5124

Client: South Broad Associates **Project No:** 0307050L **Date of Report:** April 7, 1997

EPA METHOD 8021

Matrix Type:		WATER	WATER	WATER	WATER	WATER	WATER
Date Collected:		03/13/97	03/13/97	03/13/97	03/13/97	03/13/97	03/13/97
Date Analyzed:		03/27/97	03/27/97	03/27/97	03/27/97	03/27/97	03/27/97
Field #:		MW-1 (R)	MW-4	MW-8	MW-12	MW-13	T.Blank
Lab #:		47-600	47-598	47-596	47-599	47-597	47-595
	MDL						
Dichlorodifluoromethane	10	BDL	BDL	BDL	BDL	BDL	BDL
Chloromethane	10	BDL	BDL	BDL	BDL	BDL	BDL
Vinyl Chloride	10	BDL	BDL	BDL	BDL	BDL	BDL
Bromomethane	10	BDL	BDL	BDL	BDL	BDL	BDL
Chloroethane	10	BDL	BDL	BDL	BDL	BDL	BDL
Trichlorofluoromethane	10	BDL	BDL	BDL	BDL	BDL	BDL
1,1-Dichloroethene	1	BDL	BDL	BDL	BDL	BDL	BDL
Methylene Chloride	1	BDL	BDL	BDL	BDL	BDL	BDL
trans-1,2-Dichloroethene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,1-Dichloroethane	1	BDL	BDL	BDL	BDL	BDL	BDL
2,2-Dichloropropane	1	BDL	BDL	BDL	BDL	BDL	BDL
cis,-1,2-Dichloroethene	1	BDL	BDL	BDL	BDL	BDL	BDL
Chloroform	1	BDL	BDL	BDL	BDL	BDL	BDL
Bromochloromethane	1	BDL	BDL	BDL	BDL	BDL	BDL
1,1,1-Trichloroethane	1	BDL	BDL	BDL	BDL	BDL	BDL
1,1-Dichloropropene	1	BDL	BDL	BDL	BDL	BDL	BDL
Carbon Tetrachloride	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2-Dichloroethane	1	BDL	BDL	BDL	BDL	BDL	BDL
Trichloroethene	1	BDL	BDL	9.0	BDL	BDL	BDL
1,2-Dichloropropane	1	BDL	BDL	BDL	BDL	BDL	BDL
Bromodichloromethane	1	BDL	BDL	BDL	BDL	BDL	BDL
Dibromomethane	1	BDL	BDL	BDL	BDL	BDL	BDL
1,1,2-Trichloroethane	1	BDL	BDL	BDL	BDL	BDL	BDL
Tetrachloroethene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,3-Dichloropropane	1	BDL	BDL	BDL	BDL	BDL	BDL
Dibromochloromethane	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2-Dibromoethane	1	BDL	BDL	BDL	BDL	BDL	BDL
Chlorobenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,1,1,2-Tetrachloroethane	1	BDL	BDL	BDL	BDL	BDL	BDL
Bromoform	1	BDL	BDL	BDL	BDL	BDL	BDL
1,1,2,2-Tetrachloroethane	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2,3-Trichloropropane	1	BDL	BDL	BDL	BDL	BDL	BDL
2-Chlorotoluene	1	BDL	BDL	BDL	BDL	BDL	BDL
4-Chlorotoluene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,3-Dichlorobenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,4-Dichlorobenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2-Dichlorobenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2-Dibromo-3-Chloropropane	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2,4-Trichlorobenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2,3-Trichlorobenzene	1	BDL	BDL	BDL	BDL	BDL	BDL

MDL = Minimum Detectable Level • BDL = Below Detection Level • UNITS = µg/L

Michael D. Zaliznock, Laboratory Director

Connecticut Certification No. PH-0647

AEGIS, INC.
Environmental Laboratory Services
2138 Silas Deane Highway * Rocky Hill * CT * Tel: (860)563-1041 * Fax: (860)529-5124

Client: South Broad Associates Project No: 0307050L Date of Report: April 7, 1997

EPA METHOD 8021

Matrix Type:		WATER	WATER	WATER	WATER	WATER	WATER
Date Collected:		03/13/97	03/13/97	03/13/97	03/13/97	03/13/97	03/13/97
Date Analyzed:		03/27/97	03/27/97	03/27/97	03/27/97	03/27/97	03/27/97
Field #:		MW-1 (R)	MW-4	MW-8	MW-12	MW-13	T.Blank
Lab #:		47-600	47-598	47-596	47-599	47-597	47-595
	MDL						
Benzene	1	BDL	BDL	BDL	BDL	BDL	BDL
Toluene	1	BDL	BDL	BDL	BDL	BDL	BDL
Ethylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
m-Xylene	1	BDL	BDL	BDL	BDL	BDL	BDL
p-Xylene	1	BDL	BDL	BDL	BDL	BDL	BDL
o-Xylene	1	BDL	BDL	BDL	BDL	BDL	BDL
Styrene	1	BDL	BDL	BDL	BDL	BDL	BDL
Isopropylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
n-Propylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
Bromobenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,3,5-Trimethylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
tert-Butylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
1,2,4-Trimethylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
sec-Butylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
p-Isopropyltoluene	1	BDL	BDL	BDL	BDL	BDL	BDL
n-Butylbenzene	1	BDL	BDL	BDL	BDL	BDL	BDL
Hexachlorobutadiene	1	BDL	BDL	BDL	BDL	BDL	BDL
Naphthalene	10	BDL	BDL	BDL	BDL	BDL	BDL

MDL = Minimum Detectable Level • BDL = Below Detection Level • UNITS = µg/L

Michael D. Zaliznock, Laboratory Director

Connecticut Certification No. PH-0647

CHAIN OF CUSTODY RECORD

Aegis, Inc. - Laboratory Services
2138 Silas Deane Highway, Rocky Hill, Connecticut 06067
Tel. (203) 563-1041 * Fax (203) 529-5124

FILE COP

PROJECT NAME: COMPLIANCE MONITORING
PROJECT NUMBER: 03070501
COMPANY: SOUTH BROAD STREET ASSOCIATES
ADDRESS: 500 S. BROAD ST. MERIDEN, CT
PHONE:
SAMPLED BY: JEFF JENKINS (print name)
(signature)
SAMPLED BY: (print name)
(signature)

SAMPLE NO.	DATE/ TIME	SAMPLE LOCATION	CONT SIZE G/P	GRAB	COMP	NO. OF CONT.	SAMPLE MATRIX	PRESERVATIVE	ANALYSES 8021	COMMENTS
	3/13/97		40mL	✓		2	W	Hcl/C	X	
00	0935	MW-1(R)	V							
	3/13/97		"	"		"	"	"	X	
7	1055	MW-4								
	3/13/97		"	"		"	"	"	X	
96	1525	MW-8								
	3/13/97		"	"		"	"	"	X	
7	1250	MW-12								
	3/13/97		"	"		"	"	"	X	
7	1410	MW-13								
	3/13/97		"	"		"	"	"	X	
95	0738	TRIP BLANK								

Relinquished By	Date/Time	Received By	Date/Time	Relinquished By	Date/Time	Received By Lab
	3/13/97 1705				3/13/97 1705	D. Ahmed
Relinquished By	**Date/Time**	**Received By**	**Date/Time**	**Relinquished By**	**Date/Time**	**Received By Lab**

Method of Shipment	REMARKS

c:forms\chain.doc

White - File Copy * Yellow - Project Manager Copy * Pink - Client Copy

APPENDIX E

HISTORICAL GROUND WATER HYDROGRAPHS

Monitoring Well Water Level Elevations

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\Hydrograph

APPENDIX F

HISTORICAL GROUND WATER QUALITY DATA GRAPHS

pH

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data

Total Barium [mg/L]

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data

Total Beryllium [mg/L]

500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data
Total Cadmium [mg/L]
500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data
Chloroform (CFM) [ug/L]
500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.
e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data
Total Copper [mg/L]
500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data
Hexavalent Chromium [mg/L]
500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data

Total Chromium [mg/L]

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data
Amenable Cyanide (mg/L)
500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data

Total Cyanide (mg/L)

500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\worldn\0307data\historical GWQ

Historical Ground Water Quality Data
1,1-Dichloroethane (11DCA) [ug/L]
500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data

Total Lead [mg/L]

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data

Total Nickel [mg/L]

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data

Total Organic Carbon (TOC) [mg/L]

500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data

Tetrachloroethylene (PCE) [ug/L]

500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\workin\0307data\historical GWQ

Historical Ground Water Quality Data

1,1,1-Trichloroethane (TCA) [ug/L]

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data

Trichloroethylene (TCE) [ug/L]

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\historical GWQ

Note: Minimum number on Y scale represents the laboratory detection limit.

Historical Ground Water Quality Data

Total Zinc [mg/L]

500 South Broad Street, Meriden, Connecticut



Note: Minimum number on Y scale represents the laboratory detection limit.

Aegis, Inc.

e:\workin\0307data\historical GWQ

APPENDIX G

HISTORICAL GROUND WATER FIELD MEASUREMENT DATA GRAPHS

Historical Ground Water Quality Field Measurements
Temperature
500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\Field GWQ

Historical Ground Water Quality Field Measurements
Dissolved Oxygen Concentration Data (parts per million)
500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\Field GWQ

Historical Ground Water Quality Field Measurements

Field pH

500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\Field GWQ

Historical Ground Water Quality Field Measurements
Specific Conductance (MicroSeimens/cm)
500 South Broad Street, Meriden, Connecticut



Aegis, Inc.

e:\workin\0307data\Field GWQ